

■主要諸元表

項目	記号	ガソリン													
		2.0トン						2.5トン						3.0トン	
		11-FG20PSVII 新小特		11-FG20PVII 大特				11-FG25PSVII 新小特		11-FG25PVII 大特				13-FG30PVII 大特	
				スタンダード		プレミアム				スタンダード		プレミアム			
		MT	AT	MT	AT	MT	AT	MT	AT	MT	AT	MT	AT	MT	AT
性	定格荷重 (kg)	2,000		2,000		2,000		2,500		2,500		2,500		3,000	
	基準荷重中心 (mm)	500		500		500		500		500		500		500	
	標準揚高 (mm) E	3,000		3,000		3,000		3,000		3,000		3,000		3,010	
	フリーリフト (mm) F	155		155		155		155		155		155		160	
	マスト傾斜角(前/後) G/H	6° /12°		6° /12°		6° /12°		6° /12°		6° /12°		6° /12°		6° /12°	
能	走行速度(無負荷時) F1 (km/h)	8.0	14.5	8.0	18.5	9.0	18.5	8.0	14.5	8.0	18.5	9.0	18.5	9.5	19.5
	走行速度(無負荷時) F2 (km/h)	14.0		18.5		18.5		14.0		18.5		18.5		19.5	
	走行速度(無負荷時) R1 (km/h)	8.0	14.5	8.0	18.5	9.0	18.5	8.0	14.5	8.0	18.5	9.0	18.5	9.5	19.5
	走行速度(無負荷時) R2 (km/h)	14.0		18.5		18.5		14.0		18.5		18.5		19.5	
	上昇速度(全負荷時) (mm/sec)	585	485	585	605	600	625	540	440	540	560	580	600	495	515
主要寸法	最小旋回半径(外側) (mm) I	2,215		2,215		2,215		2,270		2,270		2,270		2,390	
	最小直角通路幅 (mm) J	1,925		1,925		1,925		1,960		1,960		1,960		2,090	
	全長(フォーク付) (mm) A+K	3,410		3,410		3,410		3,625		3,625		3,625		3,775	
	全幅 (mm) L	1,155		1,155		1,155		1,155		1,155		1,155		1,235	
	全高(ヘッドガード) (mm) M	2,100		2,100		2,100		2,100		2,100		2,100		2,135	
	全高(最大揚高時) (mm) N	3,955		3,955		3,955		3,955		3,955		3,955		4,100	
	ホイールベース (mm) O	1,625		1,625		1,625		1,625		1,625		1,625		1,700	
	トレッド(前/後) (mm) P/Q	970/990		970/990		970/990		970/990		970/990		970/990		1,010/990	
	最低地上高(マスト下) (mm) R	120		120		120		120		120		120		145	
	車両重量 (kg)	3,325	3,360	3,325	3,360	3,335	3,370	3,680	3,710	3,680	3,710	3,690	3,720	4,195	4,230
エンジン	型式	FE		FE		F2		FE		FE		F2		F2	
	定格出力 (kW/rpm)	33.8/2,450	29.4/2,000	33.8/2,450		39.7/2,450		33.8/2,450	29.4/2,000	33.8/2,450		39.7/2,450		39.7/2,450	
	定格出力 (PS/rpm)	46/2,450	40/2,000	46/2,450		54/2,450		46/2,450	40/2,000	46/2,450		54/2,450		54/2,450	
	最大トルク (N·m/rpm)	142/1,600		142/1,600		157/1,600		142/1,600		142/1,600		157/1,600		157/1,600	
	最大トルク (kg·m/rpm)	14.5/1,600		14.5/1,600		16.0/1,600		14.5/1,600		14.5/1,600		16.0/1,600		16.0/1,600	
	総排気量 (cc)	1,998		1,998		2,184		1,998		1,998		2,184		2,184	
タイヤ	前輪	7.00-12-12PR (I)		7.00-12-12PR (I)		7.00-12-12PR (I)		7.00-12-12PR (I)		7.00-12-12PR (I)		7.00-12-12PR (I)		28x9-15-12PR (I)	
	後輪	6.00-9-10PR (I)		6.00-9-10PR (I)		6.00-9-10PR (I)		6.00-9-10PR (I)		6.00-9-10PR (I)		6.00-9-10PR (I)		6.50-10-10PR (I)	
Wタイヤ付	全幅 (mm)	1,455		1,455		1,455		1,455		1,455		1,455		1,460	
	トレッド(前) (mm)	1,105		1,105		1,105		1,105		1,105		1,105		1,105	
	車両重量 (kg)	3,420	3,455	3,420	3,455	3,430	3,465	3,775	3,805	3,775	3,805	3,785	3,815	4,250	4,285
	タイヤ(前輪)	5.50-15-8PR (I)		5.50-15-8PR (I)		5.50-15-8PR (I)		5.50-15-8PR (I)		5.50-15-8PR (I)		5.50-15-8PR (I)		6.00-15-10PR (I)	

項目	記号	ディーゼル													
		2.0トン						2.5トン						3.0トン	
		11-FD20PSVII 新小特		11-FD20PVII 大特				11-FD25PSVII 新小特		11-FD25PVII 大特				13-FD30PVII 大特	
				スタンダード		プレミアム				スタンダード		プレミアム			
		MT	AT	MT	AT	MT	AT	MT	AT	MT	AT	MT	AT	MT	AT
性	定格荷重 (kg)	2,000		2,000		2,000		2,500		2,500		2,500		3,000	
	基準荷重中心 (mm)	500		500		500		500		500		500		500	
	標準揚高 (mm) E	3,000		3,000		3,000		3,000		3,000		3,000		3,010	
	フリーリフト (mm) F	155		155		155		155		155		155		160	
	マスト傾斜角(前/後) G/H	6° /12°		6° /12°		6° /12°		6° /12°		6° /12°		6° /12°		6° /12°	
能	走行速度(無負荷時) F1 (km/h)	8.0	14.5	8.0	18.5	9.5	18.5	8.0	14.5	8.0	18.5	9.5	18.5	10.0	19.5
	走行速度(無負荷時) F2 (km/h)	14.0		18.0		18.0		14.0		18.0		18.0		19.0	
	走行速度(無負荷時) R1 (km/h)	8.0	14.5	8.0	18.5	9.5	18.5	8.0	14.5	8.0	18.5	9.5	18.5	10.0	19.5
	走行速度(無負荷時) R2 (km/h)	14.0		18.0		18.0		14.0		18.0		18.0		19.0	
	上昇速度(全負荷時) (mm/sec)	545	445	545	565	620	645	540	440	540	560	610	635	565	570
主要寸法	最小旋回半径(外側) (mm) I	2,215		2,215		2,215		2,270		2,270		2,270		2,390	
	最小直角通路幅 (mm) J	1,925		1,925		1,925		1,960		1,960		1,960		2,090	
	全長(フォーク付) (mm) A+K	3,410		3,410		3,410		3,625		3,625		3,625		3,775	
	全幅 (mm) L	1,155		1,155		1,155		1,155		1,155		1,155		1,235	
	全高(ヘッドガード) (mm) M	2,100		2,100		2,100		2,100		2,100		2,100		2,135	
	全高(最大揚高時) (mm) N	3,955		3,955		3,955		3,955		3,955		3,955		4,100	
	ホイールベース (mm) O	1,625		1,625		1,625		1,625		1,625		1,625		1,700	
	トレッド(前/後) (mm) P/Q	970/990		970/990		970/990		970/990		970/990		970/990		1,010/990	
	最低地上高(マスト下) (mm) R	120		120		120		120		120		120		145	
	車両重量 (kg)	3,450	3,480	3,450	3,480	3,465	3,495	3,805	3,835	3,805	3,835	3,820	3,850	4,325	4,355
エンジン	型式	XA		XA		HA		XA		XA		HA		HA	
	定格出力 (kW/rpm)	35.3/2,450	30.2/2,000	35.3/2,450		48.5/2,450		35.3/2,450	30.2/2,000	35.3/2,450		48.5/2,450		48.5/2,450	
	定格出力 (PS/rpm)	48/2,450	41/2,000	48/2,450		66/2,450		48/2,450	41/2,000	48/2,450		66/2,450		66/2,450	
	最大トルク (N·m/rpm)	142/1,600		142/1,600		196/1,600		142/1,600		142/1,600		196/1,600		196/1,600	
	最大トルク (kg·m/rpm)	14.5/1,600		14.5/1,600		20.0/1,600		14.5/1,600		14.5/1,600		20.0/1,600		20.0/1,600	
	総排気量 (cc)	2,522		2,522		2,977		2,522		2,522		2,977		2,977	
タイヤ	前輪	7.00-12-12PR (I)		7.00-12-12PR (I)		7.00-12-12PR (I)		7.00-12-12PR (I)		7.00-12-12PR (I)		7.00-12-12PR (I)		28x9-15-12PR (I)	
	後輪	6.00-9-10PR (I)		6.00-9-10PR (I)		6.00-9-10PR (I)		6.00-9-10PR (I)		6.00-9-10PR (I)		6.00-9-10PR (I)		6.50-10-10PR (I)	
Wタイヤ付	全幅 (mm)	1,455		1,455		1,455		1,455		1,455		1,455		1,460	
	トレッド(前) (mm)	1,105		1,105		1,105		1,105		1,105		1,105		1,105	
	車両重量 (kg)	3,545	3,575	3,545	3,575	3,560	3,590	3,900	3,930	3,900	3,930	3,915	3,945	4,380	4,410
	タイヤ(前輪)	5.50-15-8PR (I)		5.50-15-8PR (I)		5.50-15-8PR (I)		5.50-15-8PR (I)		5.50-15-8PR (I)		5.50-15-8PR (I)		6.00-15-10PR (I)	